# DAWSON

## LEGEND

Airports having Control Towers are shown in Blue, all others in Magenta. Consult Supplement Alaska for details involving airport lighting, navigation aids, and services. For additional symbol information refer to the Chart User's Guide.

### AIRPORTS

- Other than hard-surfaced runways
- Seaplane Base
- Hard-surfaced runways 1500 ft. to 8069 ft. in length
- Hard-surfaced runways greater than 8069 ft. or some multiple runways less than 8069 ft.
- Open dot within hard-surfaced runway configuration indicates approximate VOR, VOR-DME, or VORTAC location.

All recognizable hard-surfaced runways, including those closed, are shown for visual identification. Airports may be public or private.

### ADDITIONAL AIRPORT INFORMATION

- Private "(Pvt)" - Non-public use having emergency or landmark value
- Military - Other than hard-surfaced; all military airports are identified by abbreviations AFB, NAS, AAF, etc.
- Heliport Selected
- Unverified
- Abandoned - paved having landmark value, 3000 ft. or greater
- Ultralight Flight Park Selected

Services - fuel available and field tended during normal working hours depicted by use of ticks around basic airport symbol. (Normal working hours are Mon thru Fri 10:00 A.M. to 4:00 P.M. local time.) Consult Supplement Alaska for service availability at airports with hard-surfaced runways greater than 8069 ft.

Rotating airport beacon in operation Sunset to Sunrise

### AIRPORT DATA

Box indicates FAR 93 Special Air Traffic Rules & Airport Traffic Patterns.

FSS - FAR 91; NO SVFR; Location Identifier; NAME (NAM) (PNAM) - ICAO Location Indicator shown outside contiguous U.S.

Runways with Right Traffic Patterns (public use): CT - 118.3 ★ ⓒ ATIS 123.8; 285 L 72 122.95 - UNICOM; RP 23, 34; VFR Advsy 125.0; WX CAM - Weather Camera (AK); AOE - Airport of Entry

RP * Special conditions exist - see Supplement Alaska.

FSS - Flight Service Station

NO SVFR - Fixed-wing special VFR flight is prohibited.

CT - 118.3 - Control Tower (CT) - primary frequency

★ - Star indicates operation part-time. See tower frequencies tabulation for hours of operation.

ⓒ - Common Traffic Advisory Frequency (CTAF)

ATIS 123.8 - Automatic Terminal Information Service

ASOS/AWOS 135.42 - Automated Surface Weather Observing Systems (shown where full-time ATIS not available). Some ASOS/AWOS facilities may not be located at airports.

UNICOM - Aeronautical advisory station

VFR Advsy - VFR Advisory Service shown where full-time ATIS not available and frequency is other than primary CT frequency.

285 - Elevation in feet

L - Lighting in operation Sunset to Sunrise

*L - Lighting limitations exist; refer to Supplement Alaska.

72 - Length of longest runway in hundreds of feet; usable length may be less.

When information is lacking, the respective character is replaced by a dash. Lighting codes refer to runway edge lights and may not represent the longest runway or full length lighting.

### AIRPORT TRAFFIC SERVICE AND AIRSPACE INFORMATION

Only the controlled and reserved airspace effective below 18,000 ft. MSL are shown on this chart. All times are local.

- Class B Airspace
- Class C Airspace (Mode C - see FAR 91.215/AIM.)
- Class D Airspace
- Ceiling of Class D Airspace in hundreds of feet (A minus ceiling value indicates surface up to but not including that value.)
- Class E (sfc) Airspace
- Class E Airspace with floor 700 ft. above surface
- Class E Airspace with floor 1200 ft. or greater above surface that abuts Class G Airspace
- 2400 MSL / 4500 MSL - Differentiates floors of Class E Airspace greater than 700 ft. above surface.

Class E Airspace exists at 1200' AGL unless otherwise designated as shown above.

Class E Airspace low altitude Federal Airways are indicated by center line. Intersection - Arrows are directed towards facilities which establish intersection.

Total mileage between NAVAIDs on direct Airways

Class E Airspace low altitude RNAV Routes are indicated by center line. RNAV waypoint and name.

- Prohibited, Restricted, and Warning Areas; Canadian Advisory, Danger, and Restricted Areas
- Alert Area and MOA - Military Operations Area
- Special Airport Traffic Area (See FAR 93 for details.)
- ADIZ - Air Defense Identification Zone
- MODE C (See FAR 91.215/AIM.)
- National Security Area
- Terminal Radar Service Area (TRSA)
- MTR - Military Training Route

### COMMUNICATION BOXES

Underline indicates no voice on frequency. Crosshatch indicates Shutdown status. Operates less than continuous or On-Request.

- ASOS/AWOS
- HIWAS
- TWEB

Heavy line box indicates Flight Service Station (FSS). Frequencies 121.5, 122.2, 243.0 and 255.4 (Canada - 121.5, 126.7 and 243.0) are available at many FSSs and are not shown above boxes. All other frequencies are shown. Certain FSSs provide Airport Advisory Service, see Supplement Alaska.

R - Receive only

Frequencies above thin line box are remoted to NAVAID site. Other FSS frequencies providing voice communication may be available as determined by altitude and terrain. Consult Supplement Alaska for complete information.

### RADIO AIDS TO NAVIGATION

- VHF OMNI RANGE (VOR)
- VORTAC
- VOR-DME
- Other facilities, i.e., FSS Outlet, RCO, WX CAM (see Supp AK), etc.
- Non-Directional Radiobeacon (NDB)
- NDB - DME

### OBSTRUCTIONS

- 1000 ft. and higher AGL
- below 1000 ft. AGL
- Group Obstruction
- Obstruction with high-intensity lights; may operate part-time.
- 2049 - Elevation of the top above mean sea level
- (1149) - Height above ground
- UC - Under construction or reported; position and elevation unverified

NOTICE: Guy wires may extend outward from structures.

### TOPOGRAPHIC INFORMATION

- Roads & Road Markers
- Railroad
- Power Transmission Line
- Aerial Cable
- Landmark Feature - stadium, factory, school, golf course, etc.
- Outdoor Theater
- Lookout Tower; 618 (Elevation Base of Tower)
- Coast Guard Station
- Race Track
- Tank - water, oil or gas
- Oil Well; Water Well
- Mine or Quarry
- Mountain Pass; 11823 (Elevation of Pass)

(Pass symbol does not indicate a recommended route or direction of flight and pass elevation does not indicate a recommended clearance altitude. Hazardous flight conditions may exist within and near mountain passes.)

- Perennial Lake
- Non-Perennial Lake
- Dams
- Bridges and Viaducts

### MISCELLANEOUS

- Isogonic Line (2005 VALUE)
- Ultralight Activity
- Flashing Light
- Hang Glider Activity
- Marine Light
- Glider Operations
- Parachute Jumping Area (See Supplement Alaska.)
- VFR Waypoints (See Supplement Alaska for latitude/longitude.)

# DAWSON
## SECTIONAL AERONAUTICAL CHART
### SCALE 1:500,000

Lambert Conformal Conic Projection Standard Parallels 65°20' and 70°40'

Horizontal Datum: North American Datum of 1983 (World Geodetic System 1984)

43 RD EDITION EFFECTIVE 0901Z 22 OCT 2009 TO 0901Z 21 OCT 2010

Includes airspace amendments effective 22 OCT 2009 and all other aeronautical data received by 27 AUG 2009

Information on this chart will change; consolidated updates of chart changes are available every 56 days in the SUPPLEMENT ALASKA Chart Bulletin section (online at www.naco.faa.gov). Also consult appropriate NOTICES TO AIRMEN (NOTAMs) and other FLIGHT INFORMATION PUBLICATIONS (FLIPs) for the latest changes.

PUBLISHED IN ACCORDANCE WITH INTERAGENCY AIR CARTOGRAPHIC COMMITTEE SPECIFICATIONS AND AGREEMENTS, APPROVED BY: DEPARTMENT OF DEFENSE • FEDERAL AVIATION ADMINISTRATION

CONTOUR INTERVAL 1000 feet
Intermediate contours shown at 500 feet
Auxiliary contours shown at 250 foot interval

HIGHEST TERRAIN elevation is 9050 feet located at 64°43'N - 132°46'W

Spot elevation ....... • 4254
Approximate elevation ....... × 3200
Doubtful locations are indicated by omission of the point locator (dot or "x")

### MILITARY TRAINING ROUTES (MTRs)

All IR and VR MTRs are shown, and may extend from the surface upwards. Only the route centerline, direction of flight along the route and the route designator are depicted - route widths and altitudes are not shown.

Since these routes are subject to change every 56 days, and the charts are reissued every 6 to 12 months, you are cautioned and advised to contact the nearest FSS for route dimensions and current status for those routes affecting your flight.

Routes with a change in the alignment will be indicated in the Associated Data Section of the Supplement Alaska.

DoD users refer to Area Planning AP/1B Military Training Routes North and South America for current routes.


Published by the U.S. Department of Transportation
Federal Aviation Administration
National Aeronautical Charting Office
www.naco.faa.gov

FAA Product ID: SDAW
NSN 7641014099793
NGA REF. NO. SECXXDAWSON
EFF. DATE 09295


### PLOTTING DIRECT ROUTE ON NORTH/SOUTH SIDE

There are approximately two minutes of latitude overlap between the north and south sides of each sectional/WAC chart. To plot a course line from one side to the other, the user must first locate two pair of corresponding latitude tick marks, one pair on each side of the chart and follow the steps below.

STEP 1 - Draw a horizontal line (MATCH LINE) between each pair of corresponding latitude tick marks on each side of the chart just to the left or right of where your plot line crosses. (Figure 1)

STEP 2 - Decide which side of the chart has the departure or destination point closer to the edge of the chart. On that side, line up a blank piece of paper along the MATCH LINE (the paper should be completely on the chart, not extending beyond its edge).

STEP 3 - Slide the paper sideways left or right so that a side edge of the paper aligns with the departure or destination point (POINT A). Make a MARK A on edge of the paper where it meets that point.

STEP 4 - Without moving the paper, on the same edge as MARK A, extend a short line on the chart from the corner of the paper where it meets the MATCH LINE out to the edge of the chart. Make that LINE B.

STEP 5 - Turn the chart over and transfer the end of LINE B to the other side, and extend it straight to the MATCH LINE. (Figure 2)

STEP 6 - Take the sheet of paper with MARK A on it and align the (top or bottom) edge of the paper with the MATCH LINE and side edge with LINE B with the bulk of the sheet extending off of the chart. Plot a line from MARK A to the departure or destination point (POINT D).

STEP 7 - Where your plot line crosses the MATCH LINE make a MARK C. Extend a line straight from that mark to the edge of the chart.

STEP 8 - Turn the chart back over and transfer MARK C to that side and extend it to the MATCH LINE. Plot a line from MARK C to the destination. (Figure 3)

### ATTENTION

THIS CHART CONTAINS MAXIMUM ELEVATION FIGURES (MEF). The Maximum Elevation Figures shown in quadrangles bounded by ticked lines of latitude and longitude are represented in THOUSANDS and HUNDREDS of feet above mean sea level. The MEF is based on information available concerning the highest known feature in each quadrangle, including terrain and obstructions (trees, towers, antennas, etc.).

Example: 12,500 feet ............ 12⁵

### CONVERSION OF ELEVATIONS

FEET (Thousands): 0 2 4 6 8 10 12 14 16 18 20 22 24 26 28 30
METERS (Thousands): 0 1 2 3 4 5 6 7 8 9

### SPECIAL USE AIRSPACE ON DAWSON SECTIONAL AERONAUTICAL CHART

Unless otherwise noted altitudes are MSL and in feet. Time is local. "TO" an altitude means "To and including." FL - Flight Level. NO A/G - No air to ground communications. Contact nearest FSS for information.

† Other times by NOTAM. NOTAM - Use of this term in Restricted Areas indicates FAA and DoD NOTAM systems. Use of this term in all other Special Use areas indicates the DoD NOTAM system.

U.S. P-PROHIBITED, R-RESTRICTED, W-WARNING, A-ALERT, MOA-MILITARY OPERATIONS AREA

MOA - MILITARY OPERATIONS AREA

| MOA NAME | ALTITUDE* | TIME OF USE† | CONTROLLING AGENCY/ CONTACT FACILITY | FREQUENCIES |
|---|---|---|---|---|
| BUFFALO | 300 AGL TO BUT NOT INCL 7000 | 0800-1800 MON-FRI | ANCHORAGE CNTR | 133.3 322.5 |
| YUKON 1 | 100 AGL | 0800-1800 MON-FRI | ANCHORAGE CNTR | 133.1 285.4 |
| YUKON 2 | 100 AGL | 0800-1800 MON-FRI | ANCHORAGE CNTR | 133.1 285.4 |
| YUKON 3 HIGH | 10,000 | 1000-1300 MON-FRI | ANCHORAGE CNTR | 135.3 322.5 |
| YUKON 3A LOW | 100 AGL TO BUT NOT INCL 10,000 | 1000-1130 MON-FRI 1330-1500 MON-FRI | ANCHORAGE CNTR | 135.3 322.5 |
| YUKON 3B | 2000 AGL | BY NOTAM | ANCHORAGE CNTR | 135.3 322.5 |
| YUKON 4 | 100 AGL | 1000-1500 MON-FRI | ANCHORAGE CNTR | 132.7 381.6 |
| YUKON 5 | 5000 AGL | BY NOTAM | ANCHORAGE CNTR | 132.7 381.6 |

*Altitudes indicate floor of MOA. All MOAs extend to but do not include FL 180 unless otherwise indicated in tabulation or on chart.
† - Other times contact USAF SUAIS or FAA FSS, see SUAIS in Supplement Alaska.

AIRSPACE CLASSIFICATION (SEE CANADA FLIGHT SUPPLEMENT) AND OPERATIONAL REQUIREMENTS (DOD USERS, SEE DOD AREA PLANNING AP/1) MAY DIFFER BETWEEN CANADA AND UNITED STATES

NOTE: REFER TO CURRENT CANADIAN CHARTS AND FLIGHT INFORMATION PUBLICATIONS FOR INFORMATION WITHIN CANADIAN AIRSPACE

Flight Following Services are available on request and highly recommended in and around Class B, C, and TRSA areas.

### NORTH AMERICAN AEROSPACE DEFENSE COMMAND (NORAD) PROCEDURES

All aircraft operating in the U.S. national airspace, if capable, will maintain a listening watch on guard frequencies VHF 121.5 or UHF 243.0. It is incumbent upon all aviators to know and understand their responsibilities if intercepted. Review "AIM" section 5-6-2 for intercept procedures. Additionally, if U.S. military fighter jets intercept an aircraft and flares are dispensed in the area of that aircraft, aviators will pay strict attention, contact air traffic control immediately on the local frequency or on VHF guard 121.5 or UHF 243.0 and follow the interceptor visual ICAO signals. Be advised that non-compliance may result in the use of force.

FOR PROCUREMENT CONTACT:
FAA, National Aeronautical Charting Office
Distribution Division, ATO-W
10201 Good Luck Road
Glenn Dale, MD 20769-9700
Online at www.naco.faa.gov
Email 9-AMC-Chartsales@faa.gov
Telephone 1-800-638-8972
Fax 301-436-6829
or any authorized FAA Chart Agent




CAUTION: This chart is primarily designed for VFR navigational purposes and does not purport to indicate the presence of all power transmission and telecommunication lines, terrain or obstacles which may be encountered below reasonable and safe altitudes.

CAUTION: Severe turbulence may occur over rugged terrain. See AIM.

NAUTICAL MILES / STATUTE MILES / KILOMETERS

### REPORTING CHART ERRORS

You are requested to inform us of chart errors and/or additions that come to your attention while using this chart. Telephone toll free at 1-800-626-3677, or email us at 9-AMC-Aerochart@faa.gov. Frequently asked questions (FAQs) are answered on our website at www.naco.faa.gov. See the FAQs prior to contact via toll free number or email. Where delineation of data is required such information should be depicted clearly and accurately on a current chart, a replacement copy will be returned. Mail to: FAA, National Aeronautical Charting Office, ATO-W, SSMC-4, Sta. #2335, 1305 East West Highway, Silver Spring, MD 20910-3281.

Class G Airspace within the United States extends up to 14,500 feet MSL. At and above this altitude all airspace is within Class E Airspace, excluding the airspace less than 1500 feet above the terrain and certain special use airspace areas.

### REGULATIONS REGARDING FLIGHTS OVER CHARTED NATIONAL PARK SERVICE AREAS, U.S. FISH AND WILDLIFE SERVICE AREAS, AND U.S. FOREST SERVICE AREAS

CAUTION: Before landing fixed-wing aircraft on the lands or waters within the boundaries of lands administered by the National Park Service (NPS) and U.S. Fish and Wildlife Service (FWS), pilots should check with the respective agencies for any closures that may be in effect. The landing of helicopters is prohibited on the lands and waters within the boundaries of the lands administered by the NPS, FWS, and U.S. Forest Service (USFS) Wilderness areas. Contact information for any portions of these areas contained on this Sectional Chart can be found in the chart margin. For contact information for all these areas in Alaska, see Supplement Alaska (Area Notices).

All aircraft are requested to maintain a minimum altitude of 2,000 feet above the surface of lands and waters administered by the NPS, FWS, or USFS Wilderness areas. FAA Advisory Circular (AC) 91-36, "Visual Flight Rules (VFR) Flight Near Noise Sensitive Areas," defines the surface as: the highest terrain within 2,000 feet laterally of the route of flight, or the uppermost rim of a canyon or valley.

Pilots are warned that it is unlawful at any altitude to use an aircraft to harass any wildlife (16 USC 742j-1; 50 CFR Part 19). Harass is defined to mean disturb, worry, molest, rally, concentrate, harry, chase, drive, herd or torment.

Arctic NWR - Fairbanks, AK - (907) 456-0250
Yukon Flats NWR - Fairbanks, AK - (907) 456-0440
Yukon-Charley Rivers National Preserve - (907) 457-5752 / (907) 644-3626 (Chief Ranger)

Boundary of National Park Service areas, U.S. Fish and Wildlife Service areas, U.S. Forest Service areas.

Features normally used as checkpoints for controlling VFR traffic are emphasized on this series of charts so they may be readily identified.

Example: POWER PLANT

The name shown is that used by the controlling personnel and is not necessarily the official name of the feature.